



APPROVED BY \_\_\_\_\_  
 COMPANY: \_\_\_\_\_  
 PURCHASING/ENGINEER: \_\_\_\_\_  
 DATE: \_\_\_\_\_

Note: P1 and P2 Inside the molded must use copper foil and solder the braid 360 degree to the shell .  
**Double side " UEI " LOGE**

P1	P2 Color	P1	P2 Color	P1	P2 Color
1	1 Black	14	14 Orange/Black	27	27 Blue/Red
2	2 Black/Brown	15	15 Orange/Red	28	28 Blue/White
3	3 Black/Green	16	16 Orange/Green	29	29 Blue/White Black
4	4 Black/White	17	17 Orange/Blk. Green	30	30 IBlue/White Orange
5	5 Black/White Brown	18	18 Orange/Blue White	31	31 White
6	6 Black/White Orange	19	19 Orange/ White Black	32	32 White/Black
7	7 Red	20	20 Green	33	33 White/Red
8	8 Red/Black	21	21 Green/Black	34	34 White/Red Black
9	9 Red/Green	22	22 Green/White	35	35 White/Orange Red
10	10 Red/White	23	23 Green/Black Orange	36	36 White/Green Red
11	11 Red/Black Green	24	24 Green/White Black	37	37 White/Blue Red
12	12 Red/White Black	25	25 Blue	S	S D.W+Braid
13	13 Orange	26	26 Blue/Black		

Item	DESCRIPTION	UNIT	QTY
6	Label, Mark with p/n and rev.	PCS	1
5	PVC : 45P PVC , Color: Black/BK01-A .	G	40
4	Screw :4.0*30.5mm ( #4-40UNC ) Material Screw .	PCS	4
3	P2 CONN: DB 37Pin Female Inside Black, Pin: Gold Flash.	PCS	1
2	P1 CONN: DB 37Pin Male Inside Black, Pin: Gold Flash.	PCS	1
1	Cable: UL2464 26AWG(7/0.16TC)*37C+AL/MY+D.W+Braid, OD=9.2±0.15mm, Jacket Color: Black/BK01-A.	M	1.0

X ±	X° ±	NAME:	<b>UEI</b>		
.X ±	.X° ±	W1			
.XX ±	.XX° ±	UNITS:	PART NO.:	TITLE:	
		mm	UEI-DNA-CBL-37-RA	ASS'Y CABLE	
			Tom	DWG NO.:	
			2013.01.07	RFQ#UEI2121214-01	
		APPD BY	CHECK BY	DRAWN BY	SCALE SHEET REV.
					NONE 1/1 A

